



KOOL KAT[®] ALUMINUM WHEELS



Bring some Cool Factor to your ride with Ultima[®] Kool Kat[®] wheels. CNC Machined, Polished Aluminum wheels deliver uncompromised style that you can expect from an Ultima[®] product. Available in 16", 18", 21", 23" & 26" front & rear wheel applications. Complete the look with matching polished stainless steel Kool Kat[®] rotors & Kool Kat[®] polished pulleys.

KOOL KAT[®] FRONT WHEELS

PART NUMBER	RIM SIZE	DISC	ROTOR	BEARING TYPE	AXLE SIZE
37-613	26 X 3.5	Single	00-LTR	Sealed ball	1"
37-614	26 X 3.5	Dual	00-LTR	Sealed ball	1"
37-611	23 X 3.5	Single	00-LTR	Sealed ball	1"
37-612	23 X 3.5	Dual	00-LTR	Sealed ball	1"
37-600	21 X 2.15	Single	00-LTR	Sealed ball	1"
37-601	21 X 2.15	Dual	00-LTR	Sealed ball	1"
37-602	21 X 3.5	Single	00-LTR	Sealed ball	1"
37-603	21 X 3.5	Dual	00-LTR	Sealed ball	1"
37-604	16 X 3.5	Single	00-LTR	Sealed ball	1"
37-605	16 X 3.5	Dual	00-LTR	Sealed ball	1"

KOOL KAT[®] REAR WHEELS

PART NUMBER	RIM SIZE	ROTOR	BEARING TYPE	AXLE SIZE
37-606	16 X 3.5	00-LTR	Sealed ball	1"
37-607	18 X 3.5	00-LTR	Sealed ball	1"
37-608	18 X 5.5	00-LTR	Sealed ball	1"

KOOL KAT[®] PULLEYS

99'-EARLIER & 00'-LATER

94-630	Pulley, polished, 1.5", 70T.
94-631	Pulley, polished, 1.5", 65T.
94-632	Pulley, polished, 1-1/8", 70T.
94-633	Pulley, polished, 1-1/8", 65T.
94-634	Pulley, polished, 1", 70T.
94-635	Pulley, polished, 1", 65T.

KOOL KAT[®] ROTORS (POLISHED STAINLESS STEEL)

90-770	Rotor, 11.5" Front, 84'- 99' & 00'-later (w/speedo notch)
90-771	Rotor, 11.5" Rear, 84'- 99' & 00'-later
90-790	Rotor, 11.8" Front, 08'- 13' Touring & 06'- 09' Dyna
90-791	Rotor, 11.8" Rear, 08'- 13' Touring & 06'- 09' Dyn

Rotors & Pulleys utilize reducer spacers to achieve multi-year applications. Rotors have 2.220" center hole. Reducer spacer has 1.975" center hole.

Use MW# 33-295 Axle Reducer for 3/4" axle applications.

